


# Sluitring WS1528-IKO - WS1528-IKO

<https://www.123kogellager.nl/accessoires/ringen/sluitring/ws1528-iko>

**IKO**  
**THRUST BEARINGS**  
Thrust Needle Roller Bearings



Shaft dia. mm	Identification number							
	Thrust needle roller bearing	Mass (Ref.) g	Thrust washers	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g	
15	NTB 1528	4.1	AS 1528	3.4	WS 1528	GS 1528	9.3	

Boundary dimensions mm							Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>	
d	D	s	B	r <sub>s</sub> min	C <sub>1</sub>	C <sub>0</sub>				
15	28	2	1	2.75	0.3	18	26	8 830	29 900	12 000

Notes: (1) Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952298788
Binnendiameter	15 mm
Buitendiameter	28 mm
Dikte	2.75 mm
Materiaal	STAAL
Gewicht	9 g
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE